

Guide to the Seabrake Tow Kit from Sea Teach

The Seabrake tow kit supplied by Sea Teach consists of:

- 10mm galvanised chain
- Braid-on-braid rope tow line
- Braid-on-braid bridle
- 2 x 10mm stainless steel shackles
- 1 hard eye splice, 1 soft eye splice

The table below shows the lengths for each size of Seabrake

Model	Chain Size	Chain Length	Rope Ø	Tow Line Length	Total Bridle Length	Shackles
GP24	10mm	2.5m	14mm	35m	15m	10mm
GP30	10mm	3.0m	16mm	45m	20m	10mm
GP48	10mm	3.7m	18mm			
GP60	Please contact us for tow kits for GP60 Seabrakes					

Please note: If you wish to make your own tow kit it is vital that you use LOW STRETCH rope and NOT mooring or anchor warp.

JM plan. Use 100 metre drum of 12mm Dyeema for strength and low stretch in smaller line which fits existing gear.

Bridle requires 20M, (double duty as spare halyard est. 25 metres) so **make bridle arm 25M**

Tow line length 35 metres + 20M of bridle = 55M required. **Leave it at 75metres for the moment** for rode length flexibility. Potential to cut off 20 metre bridle later, then would leave a spare 25metre length for whatever use. **The 75 metre length may be useful as anchor or tow line.**
